AFCRC-TN-59-187

ASTIA DOCUMENT NO. AD 215064

NEW YORK UNIVERSITY

Institute of Mathematical Sciences

Division of Electromagnetic Research

NEW YORK UNIVERSITY
INSTITUTE OF MATHEMATICAL SCIENCES
LIBRARY

25 Waverly Place, New York 3, N.Y.

RESEARCH REPORT No. EM-132

Bounds on the Elements of the Equivalent Network for Scattering in Waveguides

I. Theory

LARRY SPRUCH and RALPH BARTRAM

Contract No. AF 19(604)5238

APRIL, 1959

6.1

NEW YORK UNIVERSITY
INSTITUTE OF MATHEMATICAL SCIENCES
LIBRARY
25 Waverly Place, New York 3, N. Y.

NEW YORK UNIVERSITY
Institute of Mathematical Sciences
Division of Electromagnetic Research
Research Report No. EM-132

BOUNDS ON THE ELEMENTS OF THE EQUIVALENT NETWORK
FOR SCATTERING IN WAVEGUIDES

I. THEORY

Larry Spruch and Ralph Bartram

Larry Spruch
Larry Spruch

Ralph Bartram
Ralph Bartram

Sidney Borowitz
Sidney Borowitz
Acting Project Director

Otto C. Kern Jr.
Dr. Werner Gerbes
Contract Monitor

The research reported in this document has been sponsored by the Electronics Research Directorate of the Air Force Cambridge Research Center, Air Research and Development Command. This report is intended only for internal management uses of the contractor and the Air Force.

Contract No. AF 19(604)5238

April, 1963

NEW YORK UNIVERSITY
INSTITUTE OF MATHEMATICAL SCIENCES
LIBRARY
25 Waverly Place, New York 3, N. Y.

Requests for additional copies by Agencies of the Department of Defense, their contractors and other Government agencies should be directed to the:

ARMED SERVICES TECHNICAL INFORMATION AGENCY
DOCUMENTS SERVICE CENTER
ARLINGTON HALL STATION
ARLINGTON 12, VIRGINIA

Department of Defense contractors must be established for ASTIA services or have their 'need-to-know' certified by the cognizant military agency of their project or contract. All other persons and organizations should apply to the:

U.S. DEPARTMENT OF COMMERCE
OFFICE OF TECHNICAL SERVICES
WASHINGTON 25, D.C.

Abstract

For a few particular waveguide problems, standard variational expressions have previously been shown to be upper or lower bounds on the quantities of interest. However, bounds have not previously been obtained for any truly three dimensional problem, that is, where the fields cannot be derived from a single scalar potential. An example is a three dimensional obstacle which contacts only one waveguide surface. As one consequence, no straightforward procedure exists for improving the approximations. Recently, Kato devised a rather general method for bounding the cotangent of the phase shift for a given angular momentum in a quantum mechanical central potential scattering problem. This method should be applicable whenever a system can be analyzed in terms of uncoupled standing waves each characterizable by one real phase shift. The method is here adapted to waveguides, including truly three dimensional problems. The obstacle must be symmetric about a plane perpendicular to the waveguide axis, with certain exceptions only one mode should propagate, and the system should be lossless. Analysis is then possible in terms of η_e^* and η_o , the real uncoupled phase shifts associated with the even and odd standing waves, respectively. The bounds obtained on $\cot\eta_e$ and $\cot\eta_o$ determine bounds on the equivalent network elements.

Table of Contents

	<u>Page</u>
1. Introduction	1
2. Applicability of the Kato method	3
3. Variational principles for waveguides	9
4. Rigorous bounds on the error	13
5. Completeness	17
6. Lower bounds on α_θ and β_θ	21
References	25
Distribution List	

1. Introduction

The introduction of variational techniques has greatly facilitated the solution of scattering problems in various fields. They were originally applied by Schwinger to scattering in an analysis of waveguide problems^{1,2} and quantum mechanical problems³ and, independently, by Hulthén⁴ in an analysis of quantum mechanical problems.⁵ These techniques have subsequently proved to be useful in a wide variety of fields including optics, acoustics and water waves. Though they are clearly superior to previously-used techniques, variational techniques as applied to scattering theory suffer a major defect as compared to variational techniques as applied to the determination of point eigenvalues such as the resonant frequencies of vibrating systems or the bound state energy eigenvalues of quantum mechanical systems. This defect is that while the expressions are stationary, they are in general neither an upper nor a lower bound. Thus, given two different trial functions, one cannot generally know which of the two variational results is better; in particular, the incorporation of additional parameters in a given trial function does not guarantee a better result. Consequently, it would be desirable to be able to deduce bounds on the quantities of interest. Now, in fact in some particular waveguide problems the variational expressions themselves have been shown to be upper or lower bounds.^{1,2} These problems are not sufficiently general, however, to include all cases of practical interest. For example, no technique seems to have been devised which is capable of giving bounds on the relevant quantities for a truly three-dimensional case, that is, where the fields cannot be derived from a single scalar potential.

Now a rather general approach has been devised by T. Kato^{6,7,8,9} for obtaining bounds on $\cot (\eta - \theta)$, where η is the phase shift for a given angular momentum in a quantum mechanical central potential scattering problem and θ is a parameter chosen for convenience. This method should be applicable to any problem which can be analysed in terms of uncoupled standing waves each of which can be characterized by one real phase shift. It is the purpose of this paper to adapt the Kato formalism to scattering by obstacles in waveguides, including the truly three dimensional problem. The problems to be considered, for reasons which will be discussed later, are subject to the following restrictions:

- (1) The waveguide is uniform in the asymptotic region.
- (2) Only the dominant mode propagates, with exceptions which will be mentioned later.
- (3) The obstacle is symmetrical about a plane perpendicular to the axis of the waveguide.
- (4) The waveguide and obstacle are lossless.

In the companion paper,¹⁰ the Kato formalism is applied to some specific problems involving dielectric obstacles and it is found that with a simple trial function and a moderate amount of work one can obtain upper and lower bounds on $\cot (\eta_o - \theta)$ and $\cot (\eta_e - \theta)$ where η_e and η_o are the real uncoupled phase shifts associated with the even and odd standing waves, respectively. These bounds differ from one another by only a few per cent, even for obstacles whose dimensions are comparable with the transverse dimensions of the waveguide. In addition, for the obstacles considered, bounds can be obtained directly on the phase shifts themselves and on the elements of the equivalent 'T' network.

2. Applicability of the Kato method

Before proceeding to the waveguide case, it will be helpful to outline Kato's approach. A standard technique in the quantum theory of scattering of a particle by a central potential, $V(\underline{r}) = V(r)$, is to separate the wave into partial waves, i.e., the eigenfunctions of the angular momentum operator. For a specified angular momentum and energy, the effect of the potential on each incident partial wave is completely characterized by one real number, the phase shift. For the case of zero orbital angular momentum, which is the closest analogue to the waveguide case we are ultimately interested in, the phase shift η is determined by the equations

$$\mathcal{L}' u_{\theta} = \left[\frac{d^2}{dr^2} + k^2 + W(r) \right] u_{\theta} = 0 \quad , \quad 0 \leq r \leq \infty \quad (1a)$$

$$u_{\theta}(0) = 0 \quad (1b)$$

$$u_{\theta}(r) \rightarrow \cos(kr+\theta) + \cot(\eta-\theta) \sin(kr+\theta) \quad , \quad r \rightarrow \infty \quad (1c)$$

In the above expressions, k^2 and $W(r)$ are proportional to the total energy and the negative of the potential energy, respectively, and the normalization constant θ satisfies $0 \leq \theta < \pi$ but is otherwise arbitrary. The introduction of θ provides an additional element of freedom.

Let u_{θ_t} be a trial wave function which satisfies the boundary condition (1b) and has the asymptotic form (1c) with a trial phase shift η_t , but which does not satisfy the wave equation (1a). (Trial quantities will be distinguished

from their exact counterparts by a subscript t.) From Green's theorem,

$$\int_0^{\infty} (u_{\theta} \mathcal{L}' u_{\theta t} - u_{\theta t} \mathcal{L}' u_{\theta}) dr = \left[u_{\theta} \frac{du_{\theta t}}{dr} - u_{\theta t} \frac{du_{\theta}}{dr} \right]_0^{\infty}, \quad (2)$$

and the asymptotic forms of u_{θ} and $u_{\theta t}$, it follows that

$$k \cot(\eta - \theta) = k \cot(\eta_t - \theta) - \int u_{\theta t} \mathcal{L}' u_{\theta t} dr + \int w_{\theta} \mathcal{L}' w_{\theta} dr, \quad (3)$$

where

$$w_{\theta}(r) = u_{\theta t}(r) - u_{\theta}(r). \quad (4)$$

Equation (3) is an identity. If $u_{\theta t}$ is a good approximation to u_{θ} , then w_{θ} is a small term of first order, and the error term $\int w_{\theta} \mathcal{L}' w_{\theta} dr$ is of second order. If the error term is neglected in equation (2), the remaining two terms on the right hand side can be evaluated explicitly and constitute a variational expression for $k \cot(\eta - \theta)$. (For certain values of θ , this expression reduces to previously known variational principles.)

Kato's major contribution was the determination of upper and lower bounds on the error term and, hence, on $k \cot(\eta - \theta)$.⁶ Kato derives the inequality

$$-\alpha_{\theta}^{-1} \int \rho^{-1} (\mathcal{L}' u_{\theta t})^2 dr \leq \int w_{\theta} \mathcal{L}' w_{\theta} dr \leq \beta_{\theta}^{-1} \int \rho^{-1} (\mathcal{L}' u_{\theta t})^2 dr \quad (5)$$

where ρ is some non-negative weight factor to be chosen for convenience; α_θ is the smallest positive eigenvalue and β_θ the smallest (in absolute value) negative eigenvalue of the associated eigenvalue problem,

$$\mathcal{L}' \phi_n(r) + \mu_n \rho(r) \phi_n(r) = 0 \quad , \quad 0 \leq r \leq \infty \quad . \quad (6)$$

The eigenfunctions ϕ_n and eigenvalues μ_n are determined by the boundary conditions that ϕ_n vanish at the origin and have the asymptotic phase shift, $\delta(\mu_n)$, given by

$$\delta(\mu_n) = \theta + n\pi \quad , \quad n = 0, \pm 1, \dots \quad . \quad (7)$$

Even quite crude lower bounds on α_θ and β_θ in equation (5) will provide close bounds on the error term in equation (3) and, hence, on the phase shift, provided the error integral, $\int \rho^{-1} (\mathcal{L}' u_{\theta t})^2 dr$, which vanishes for the exact wave function, can be made sufficiently small. Comparison potentials for which equation (6) can be solved exactly are employed in the estimation of α_θ and β_θ , together with a theorem which states that the phase shift increases monotonically with increasing 'potential', $W(r)$ ^{6,7,8} (decreasing potential energy).

Let us now consider a one dimensional quantum mechanical scattering problem, which is a still closer analogue to the waveguide problem. This differs from the previous case in that the range of the independent variable extends from $-\infty$ to $+\infty$. The difference is fundamental, however, since there are now two channels, i.e., two sets of incoming and outgoing waves. In a scattering problem which contains n channels, the remote effects of the scattering

process are characterized by an $n \times n$ scattering matrix relating the amplitudes of the n outgoing waves to those of the n incoming waves. Since the n^2 elements of the scattering matrix are complex, there are $2n^2$ quantities in all. However, not all of these quantities are independent. It follows from conservation of probability (energy in the electromagnetic case) and time reversibility that the scattering matrix is unitary and symmetric, which reduces the number of independent quantities to $\frac{1}{2}n(n+1)$.^{11,12} In the case of scattering by a central potential, there is a channel corresponding to each value of the angular momentum, but since the potential does not couple the waves of different angular momentum there is a separate scattering problem for each channel characterized by a single number, the phase shift. In the one dimensional problem there are two channels; hence three independent quantities are required to characterize the scattering. For this case, the Kato method does not appear to be applicable. However, if we restrict ourselves to an even 'potential', $W(x) = W(-x)$, the number of independent parameters is reduced to two. Further, the two independent solutions of the wave equation can be taken as standing waves which are even and odd in x , each characterized by one real number, the phase shifts η_e and η_o , respectively. The even and odd solutions can be regarded as solutions to two completely independent scattering problems, distinguished by the boundary conditions. The odd solution is identical with the solution of the radial wave equation for zero angular momentum (an odd function vanishes at the origin) except that the integrals are multiplied by $\frac{1}{2}$ because the range of integration has been doubled. The Kato method can also be applied to the even solution with minor modifications. The details will not be presented here because of the close correspondence to the waveguide case which will now be treated.

In the waveguide problem two additional formal complications arise. Firstly, the problem is three dimensional so that the line integrals which appear in the variational principle are replaced by volume integrals. Secondly, the wave functions are vectors rather than scalars. It will be seen that these two complications do not cause any difficulty in principle; in particular, the assumed uniformity of the waveguide in the asymptotic region makes the problem effectively one dimensional in this region. However, there are two channels corresponding to each propagating mode. If the Kato method is to be applicable, then in line with the previous discussion the waveguide and obstacle must be such that it is possible to reduce the scattering problem to completely independent problems each characterized by one real number. The number of channels can be reduced to two by requiring that the waveguide have only one propagating mode, which is not a serious restriction in most applications. Then, as in the one dimensional case, the number of independent parameters can be reduced from three to two and the scattering problem to completely independent problems for even and odd solutions if the obstacle is symmetrical about a plane perpendicular to the axis of the waveguide.

More than one mode can be allowed to propagate if the obstacle is such that it does not couple these modes. As an example, consider a metallic or uniform dielectric obstacle in a rectangular waveguide in the form of a right circular cylinder parallel to the direction of polarization of the dominant mode, centered in the guide and extending between the conducting boundaries. It is possible to select the dimensions of the waveguide in such a way that in some range of frequencies there are only three propagating modes, usually designated TE_{10} , TE_{20} and TE_{01} .¹² These three modes are not coupled to one

another by such an obstacle, nor are the even and odd standing wave solutions corresponding to each mode coupled. Thus there is a total of six channels such that the scattering in each channel is a separate problem characterized by a single phase shift. A simpler example is that of a dielectric obstacle whose permittivity is an even function of the coordinate parallel to the axis of the waveguide only. The problem is then one dimensional and we can consider an arbitrary number of propagating modes. For the various channels are uncoupled and each is characterized by a single phase shift. The problem of multiple propagating modes will not be considered further. It will henceforth always be understood that just the dominant mode propagates.

In some cases the symmetry of the obstacle is such that the scattering can be described in terms of a scalar wave function rather than a vector wave function, which may result in considerable simplification. For example, in a rectangular waveguide the dominant mode can be described variously as a TE wave propagating parallel to the axis of the waveguide, as a TM wave propagating parallel to the axis of polarization, or as a TE wave propagating in a direction perpendicular to both of these axes. Any finite obstacle destroys uniformity in the direction of the waveguide, but it may possess sufficient symmetry to preserve uniformity in one of the perpendicular directions, in which case the TE or TM description still applies. Now TE and TM waves can be derived from Hertzian electric and magnetic vector potentials, respectively, which are parallel to the propagation direction of the TE and TM waves respectively. Thus the fields are characterized by a single scalar function, the component along the appropriate axis of propagation of the Hertzian vector potential.

If the symmetry of the obstacle permits description of the fields in terms of a TM wave propagating parallel to the axis of polarization, the electric field is proportional to the vector potential, and the vector equations derived below go over to scalar equations directly. For the symmetry which permits description in terms of a TE wave, there is no such simple correspondence and the scalar formulation of the problem requires a separate derivation starting directly from the Hertzian vector potential formulation. Only the vector formulation will be presented here, though in the TE case it might be simpler to use the scalar formulation.

3. Variational principles for waveguides

In this section we shall derive the variational principle for a waveguide for both metallic and dielectric obstacles, with the four restrictions noted in the Introduction. In line with the previous discussion, it then follows that the general scattering problem reduces to two independent scattering problems, each of which can be characterized by just one real phase shift.

Assuming a time dependence $\exp(-i\omega t)$, the electric field intensity, $\underline{E}(\underline{r})$, satisfies the equations

$$\mathcal{L}\underline{E} = -\underline{\nabla} \times \underline{\nabla} \times \underline{E} + (\omega^2/c^2 + W)\underline{E} = 0 \quad (8a)$$

$$\underline{\nabla} \cdot \underline{E} = 0 \quad (8b)$$

where c is the velocity of light, ϵ is the relative permittivity, and where the 'potential' W is defined by $W = \omega^2(\epsilon - 1)/c^2$; the quantum mechanical analogue of W is proportional to the negative of the potential. In addition, $\underline{E}$ is required to be normal to all conducting surfaces including any metallic obstacles.

Let the z -coordinate be parallel to the axis of the waveguide. It follows from restriction (3) that $W(z) = W(-z)$, and the general solution can be expressed as a linear combination of standing wave solutions which are even and odd functions of z . In what follows, subscripts e and o will be used to denote quantities associated with the even and odd functions respectively, but will be omitted wherever the formalism is the same for both functions. The solutions are required to have the asymptotic forms for $z \rightarrow +\infty$

$$\underline{E}_{\theta e}(\underline{r}) = \underline{e}(x,y) \left| -\sin(kz+\theta) + \cot(\eta_e - \theta) \cos(kz+\theta) \right| \quad (9a)$$

$$\underline{E}_{\theta o}(\underline{r}) = \underline{e}(x,y) \left| \cos(kz+\theta) + \cot(\eta_o - \theta) \sin(kz+\theta) \right| \quad (9b)$$

where $\underline{e}(x,y)$ is the form function for the dominant mode and where θ satisfies $0 \leq \theta < \pi$. The utility of the parameter θ will become apparent as we go along.

The trial functions are distinguished from the exact functions by the subscript t , and are required to be even and odd and to have the asymptotic forms given by equations (9) except for the substitution of trial phase shifts η_{et} and η_{ot} for the exact phase shifts η_e and η_o . In addition, the trial function is required to be normal to all conducting surfaces and both the function and first derivatives are required to be continuous in the interior of the waveguide.

Consider the integral

$$\int (\underline{E} \cdot \mathcal{L} \underline{E}_t - \underline{E}_t \cdot \mathcal{L} \underline{E}) d\tau = - \int (\underline{E} \cdot \underline{\nabla} \times \underline{\nabla} \times \underline{E}_t - \underline{E}_t \cdot \underline{\nabla} \times \underline{\nabla} \times \underline{E}) d\tau \quad (10)$$

where the range of integration is over the interior of the waveguide. (It is to be understood, from here on, that 'the interior of the waveguides' excludes any metallic obstacles.) The second term in the integrand on the left hand side of equation (10) vanishes by virtue of equation (8a), and the right hand side can be transformed by Green's theorem to give

$$\int \underline{E} \cdot \mathcal{L} \underline{E}_t d\tau = \int (\underline{E} \times \underline{\nabla} \times \underline{E}_t - \underline{E}_t \times \underline{\nabla} \times \underline{E}) \cdot \underline{d}\sigma \quad . \quad (11)$$

The surface integral vanishes on the conducting surfaces since $\underline{E}$ and $\underline{E}_t$ are required to be normal to these surfaces, and the contribution from the asymptotic region is

$$\int \underline{E}_\theta \cdot \mathcal{L} \underline{E}_{\theta t} d\tau = 2k \left[\cot(\eta_t - \theta) - \cot(\eta - \theta) \right] \int \left[\underline{e}(x,y) \times \underline{a}_z \right]^2 d\sigma \quad (12)$$

where $\underline{a}_z$ is the unit vector in the z direction and the surface integral is over the cross section of the wave guide. It is convenient at this point to adopt a normalization and notation conforming more closely to that of Kato.⁶ Let $\underline{u}_\theta$ and $\underline{w}_\theta$ be defined by

$$\underline{u}_\theta \equiv \left\{ \int \left[\underline{e}(x,y) \times \underline{a}_z \right]^2 d\sigma \right\}^{-\frac{1}{2}} \underline{E}_\theta \quad (13a)$$

$$\underline{w}_\theta = \underline{u}_{\theta t} - \underline{u}_\theta \quad (13b)$$

With these definitions, equation (12) can be written as

$$k \cot(\eta - \theta) = k \cot(\eta_t - \theta) - \frac{1}{2} \int \underline{u}_{\theta t} \cdot \mathcal{L} \underline{u}_{\theta t} d\tau + \frac{1}{2} \int \underline{w}_{\theta} \cdot \mathcal{L} \underline{w}_{\theta} d\tau \quad (14)$$

in analogy with equation (3). The factor $\frac{1}{2}$ arises because the range of integration has been doubled. The first two terms on the right hand side of equation (14) can be calculated by specifying the trial function, and constitute a variational approximation for $k \cot(\eta - \theta)$. The third term, $\frac{1}{2} \int \underline{w}_{\theta} \cdot \mathcal{L} \underline{w}_{\theta} d\tau$, is the error term and is of the order of the square of the error in the trial function.

We now derive one consequence of equation (14). We have η as the phase shift associated with W . We let $\eta + d\eta$ be the phase shift associated with $W + dW$, where $dW(r) \geq 0$ for all r . Applying equation (14) to the determination of $\eta + d\eta$, we choose for our trial function the exact solution $\underline{u}_{\theta}$ associated with W . We find

$$d\eta = \left(\frac{1}{2} \sin^2 \eta / k \right) \int \underline{u}_{\theta}^2(r) dW(r) dr \geq 0 \quad .$$

where the inequality is a consequence of the non-negativeness of $dW(r)$ and the reality of $\underline{u}_{\theta}(r)$. More generally, it then follows that if $W_2(r) \geq W_1(r)$, then $\eta_2 \geq \eta_1$. This result is generally referred to as the monotonicity theorem.

4. Rigorous bounds on the error

Kato's method for obtaining rigorous bounds on the error term, and hence on $\cot(\eta-\theta)$, can be applied to the waveguide case with minor modification.

In order to accomplish this, we make use of the following information about $\underline{w}_\theta$:

$$\mathcal{L}\underline{w}_\theta = \mathcal{L}\underline{u}_{-\theta t} \quad (15a)$$

$$\underline{w}_{\theta e} \rightarrow C'_e \underline{e}(x,y) \cos(kz+\theta) \quad , \quad z \rightarrow +\infty \quad (15b)$$

$$\underline{w}_{\theta o} \rightarrow C'_o \underline{e}(x,y) \sin(kz+\theta) \quad , \quad z \rightarrow +\infty \quad (15c)$$

where C'_e and C'_o are unknown constants. Also, $\underline{w}_{\theta e}$ and $\underline{w}_{\theta o}$ are even and odd functions of z respectively; $\underline{w}_\theta$ is normal to all conducting surfaces, and $\underline{w}_\theta$ and its first derivatives are continuous in the interior of the waveguide. Consider the equation

$$\mathcal{L}\underline{\phi}(\underline{r}) + \mu\rho(\underline{r})\underline{\phi}(\underline{r}) = 0 \quad (16)$$

The function $\underline{\phi}(\underline{r})$ is required to be normal to all conducting surfaces. The weight function $\rho(\underline{r}) \geq 0$ is an even function of z and tends to zero at large distances from the obstacle in such a way that $\int \rho(\underline{r})d\mathbf{r}$ converges. Equation (16) may be regarded as a scattering problem of the type of equation (8), with a 'potential' $W + \mu\rho$. The even and odd standing wave solutions are associated with entirely separate problems and the distinction between them is not relevant to the following discussion. Let $\delta(\mu)$ be the phase shift corresponding to this 'potential'. (The choice of ρ must be such that this problem also

satisfies the four restrictions listed in the introduction in order that there be just one phase shift $\delta(\mu)$ associated with each value of μ .) Equation (16) will be referred to as the associated eigenvalue problem with eigenvalues μ_n and eigen functions $\phi_n(\underline{r})$ when $\delta(\mu_n)$ is restricted by the condition

$$\delta(\mu_n) = \theta + n\pi \quad . \quad (17)$$

If $\underline{f}$ and $\underline{g}$ are two functions which satisfy the boundary conditions appropriate to ϕ_n , then it follows from Green's theorem that

$$\int \underline{f} \cdot \mathcal{L} \underline{g} \, d\tau = \int \underline{g} \cdot \mathcal{L} \underline{f} \, d\tau \quad (18)$$

where the integrals are over the interior of the waveguide. Thus the operator $\mathcal{L}$ restricted by these boundary conditions is hermitean; it follows that the eigenvalues are real and the eigenfunctions satisfy orthogonality relations

$$k \int \underline{\phi}_m \cdot \underline{\phi}_n \rho \, d\tau = \delta_{mn} \quad (19)$$

where $\delta_{mn} = 1$ if $m = n$ and $\delta_{mn} = 0$ if $m \neq n$ and the normalization is chosen for convenience.

Using the monotonicity theorem discussed earlier, it follows since $\rho(r) \geq 0$ for all r that

$$\frac{d\delta(\mu)}{d\mu} \geq 0 \quad . \quad (20)$$

The eigenvalues therefore satisfy the relationship

$$\mu_{n+1} \geq \mu_n . \quad (21)$$

It can be shown that the eigenfunctions $\underline{\phi}_n$ form a complete set in the sense that the Parseval identities hold for any functions $\underline{F}$, $\underline{G}$ which satisfy certain symmetry conditions to be discussed in the following section, which are normal to all conducting surfaces and which are continuous and have continuous first derivatives, that is

$$\begin{aligned} k \int \underline{F}^2 \rho \, d\tau &= \sum a_n^2 , \quad k \int \underline{F} \cdot \underline{G} \rho \, d\tau = \sum a_n b_n , \\ k \int \underline{G}^2 \rho \, d\tau &= \sum b_n^2 : \end{aligned} \quad (22)$$

the a_n and b_n are Fourier coefficients defined by

$$a_n = k \int \underline{\phi}_n \cdot \underline{F} \rho \, d\tau , \quad b_n = k \int \underline{\phi}_n \cdot \underline{G} \rho \, d\tau . \quad (23)$$

Now let $\underline{F}$ satisfy the boundary conditions (17) and set $\underline{G} = \rho^{-1} \mathcal{L} F$.

Then

$$\begin{aligned} b_n &= k \int \underline{\phi}_n \cdot \mathcal{L} \underline{F} \, d\tau = k \int \mathcal{L} \underline{\phi}_n \cdot \underline{F} \, d\tau = - \mu_n k \int \underline{\phi}_n \cdot \underline{F} \rho \, d\tau \\ &= - \mu_n a_n \end{aligned} \quad (24)$$

where we have made use of the hermitean property of $\mathcal{L}$. equation (18).

The Parseval identities become

$$k \int F^2 \rho d\tau = \sum \mu_n^{-2} b_n^2 \quad (25a)$$

$$k \int \underline{F} \cdot \mathcal{L} \underline{F} d\tau = - \sum \mu_n^{-1} b_n^2 \quad (25b)$$

$$k \int (\mathcal{L} \underline{F})^2 \rho^{-1} d\tau = \sum b_n^2 . \quad (25c)$$

Let α_θ be the smallest positive eigenvalue and $-\beta_\theta$ the smallest (in absolute value) negative eigenvalue, so that $-\alpha_\theta^{-1} \leq -\mu_n^{-1} \leq \beta_\theta^{-1}$. Then it follows from equations (25) that

$$-\alpha_\theta^{-1} \int (\mathcal{L} \underline{F})^2 \rho^{-1} d\tau \leq \int \underline{F} \cdot \mathcal{L} \underline{F} d\tau \leq \beta_\theta^{-1} \int (\mathcal{L} \underline{F})^2 \rho^{-1} d\tau . \quad (26)$$

The point is that while $\mathcal{L}$ is an unbounded operator, $\mathcal{L}^{-1}$ is a bounded operator, its eigenvalues ranging from $-\beta_\theta^{-1}$ to α_θ^{-1} . If we identify $\underline{F}$ with $\underline{w}_\theta$ defined by equation (13b) and recognize that $\mathcal{L} \underline{w}_\theta = \mathcal{L} \underline{u}_{\theta t}$, equation (26) implies that

$$-\frac{1}{2} \alpha_\theta^{-1} \int (\mathcal{L} \underline{u}_{\theta t})^2 \rho^{-1} d\tau \leq \frac{1}{2} \int \underline{w}_\theta \cdot \mathcal{L} \underline{w}_\theta d\tau \leq \frac{1}{2} \beta_\theta^{-1} \int (\mathcal{L} \underline{u}_{\theta t})^2 \rho^{-1} d\tau . \quad (27)$$

The quantity $\frac{1}{2} \int (\mathcal{L} \underline{u}_{\theta t})^2 \rho^{-1} d\tau$ is determined by specifying the trial function $\underline{u}_{\theta t}$. Thus the problem of obtaining rigorous upper and lower bounds on the error term in equation (14) is reduced to that of obtaining rigorous lower bounds on α_θ and β_θ . If the trial function $\underline{u}_{\theta t}$ is a good approximation

to the exact function $\underline{u}_\theta$, $(\mathcal{L} \underline{u}_{\theta t})^2$ is a small term of second order, and even crude lower bounds on α_θ and β_θ can provide close bounds on the error term and hence on $\cot(\eta-\theta)$.

5. Completeness

The question of completeness is rather more complicated for the present waveguide case than for the one independent variable quantum mechanical case discussed by Kato. In particular, it will be shown that the $\underline{\phi}_n$ as defined by the differential equation, (16), and by the boundary condition, equation (17), are not necessarily complete. Limitations are thereby imposed on the trial function, in addition to the boundary conditions stated in Section 3, if the bounds deduced in Section 4 on $\cot(\eta-\theta)$ are to be valid. It will be seen, however, that the limitations are in no sense severe; on the contrary, it will only be required that the trial function have the same symmetry properties as the true function. Clearly, no restrictions whatever are thereby introduced on the accuracy of the bounds that can be achieved. The fact remains that each of the symmetry properties must be recognized if the Kato bounds are to be valid.

That the $\underline{\phi}_n$ are not always complete can be seen by considering the simple example of a waveguide for which the obstacle is a dielectric slab which extends to the conducting boundaries of the waveguide and whose permittivity is independent of x and y . Then each of the $\underline{\phi}_n$ will everywhere (not only asymptotically) have the same x and y dependence. In particular, each $\underline{\phi}_n$ can be expressed as a product of $\underline{e}(x,y)$ and a function of z , where $\underline{e}(x,y)$ is the form function appropriate to the dominant mode, and the problem is then effectively one dimensional. In this example the $\underline{\phi}_n$ are obviously not a complete set; this need cause no concern, however. It is clear that the true

solution $\underline{u}$ would also have the same x,y dependence as the dominant mode.

One would then choose the trial function $\underline{u}_t$ to have this x,y dependence, in which case $\underline{w} = \underline{u}_t - \underline{u}$ would also have this x,y dependence, and this $\underline{w}$ could be expanded in terms of the ϕ_n . On the other hand, if one failed to recognize the one dimensionality of the problem and used any x,y dependence other than that given by $\underline{e}(x,y)$, $\underline{w}$ could not be expanded in terms of the ϕ_n and the bounds obtained on $\cot(\eta-\theta)$ in Section 4 would not be rigorous.

In discussing the question of completeness for an arbitrary $W(x,y,z)$, it is assumed for simplicity of presentation that W and ρ both vanish identically beyond $|z| = d$. It is believed, however, that the conclusions of this section can be established under more general circumstances. Now it can be shown that the eigenfunctions of a positive definite, hermitian operator form a complete set.¹³ Actually, the essential point is not that the operator be positive definite but rather that there be a minimum negative eigenvalue. That there is a minimum negative eigenvalue in the associated eigenvalue problem follows from the assumption that W and ρ vanish identically beyond $|z| = d$, since there is a minimum number of nodes which the wave functions can have in the region $-d < z < d$.

It remains to determine the boundary conditions for which $\mathcal{L}$ is hermitian. It follows from Green's theorem that for two functions $\underline{f}(\underline{r})$ and $\underline{g}(\underline{r})$ which are continuous and have continuous first derivatives, and which are normal to the conducting boundaries of the waveguide,

$$\int (\underline{f} \cdot \mathcal{L} \underline{g} - \underline{g} \cdot \mathcal{L} \underline{f}) d\tau = \int (\underline{f} \times \underline{\nabla} \times \underline{g} - \underline{g} \times \underline{\nabla} \times \underline{f}) \cdot d\underline{\sigma}$$

where the surface integral is over end surfaces of the waveguide in the asymptotic region. Consider a set of eigenfunctions $\underline{\psi}_m$ of the differential

equation

$$\mathcal{L} \psi_m + \lambda_m \rho \psi_m = 0 \quad ,$$

defined by the boundary condition

$$\int (\psi_m \times \nabla \times \psi_n - \psi_n \times \nabla \times \psi_m) \cdot d\sigma = 0$$

for all m and n . Then the operator $\mathcal{L}$ is hermitian with respect to the set of functions ψ_m and it follows that these functions form a complete set. The set of functions ψ_m can be divided into two subsets. The first subset consists of functions which have the asymptotic form of the dominant mode and whose phase shifts $\delta(\lambda_m)$ differ by integral multiples of π . This subset is identical with a set of associated eigenfunctions ϕ_n with $\lambda_m = \mu_n$. The second subset consists of functions which vanish asymptotically. These functions do not occur in the one independent variable quantum mechanical problem with fixed, positive energy, and it follows that for that problem each of the ψ_m equals one of the ϕ_n which then form a complete set. However, in the waveguide problem the functions which vanish asymptotically can exist under special circumstances which will now be considered.

In the region of large $|z|$, where W and ρ are zero, each ψ_m is a superposition of evanescent waveguide modes and of the dominant waveguide mode. (The term waveguide mode will be used for modes in the absence of an obstacle.) The coefficient of the dominant waveguide mode will be denoted by C_m . There are two alternative possibilities.

- (1) If each C_m is different from zero, each ψ_m equals one of the ϕ_n and each λ_m equals one of the μ_n . The ϕ_n then form a complete set.

- (2) If $C_m = 0$ for any m , the corresponding ψ_m vanishes asymptotically and the ϕ_n do not then form a complete set.

The condition $C_m = 0$ can only arise if some of the evanescent waveguide modes are not coupled to the dominant waveguide mode. This lack of coupling can only occur if W and ρ have some special symmetry property. We have already given one example in which W and ρ are independent of the transverse coordinates. As another example, we consider a rectangular waveguide where the z axis is the axis of the waveguide, the y axis is the axis of polarization of the dominant mode and the waveguide extends from $x = 0$ to $x = a$. We further specify that W and ρ are independent of y and are even functions of $x - \frac{1}{2}a$. Then the functions ϕ_n share the polarization of the dominant mode, are independent of y , and are even functions of $x - \frac{1}{2}a$; the ψ_n are not, therefore, a complete set. The set of functions ψ_m which is complete includes functions which are odd functions of $x - \frac{1}{2}a$, functions which depend upon y and whose polarization is not along the y axis, and functions with both of these properties, all of which vanish asymptotically. However, the exact solution u is also polarized parallel to the y axis, is independent of y , and is an even function of $x - \frac{1}{2}a$. If the trial function u_t is chosen to have the same properties it will be possible to expand w in terms of the incomplete set ϕ_n .

In summary, if W and ρ have no symmetry properties, the ψ_m are identical with the ϕ_n so the latter form a complete set. On the other hand, if W and ρ do have some symmetry properties, the functions ϕ_n have some common symmetry properties and do not then form a complete set. The set of functions ψ_m is complete, however, since it then contains functions which vanish asymptotically and have different symmetry properties. For an arbitrary trial function u_t the difference function w could only be expanded in terms of the ψ_m ;

one could not then use the monotonicity theorem to order the eigenvalues in terms of the phase shifts, an ordering which is essential for the applicability of the method used in the following section for the determination of bounds on α_θ and β_θ . It is of course quite possible that methods could be devised for the determination of bounds on α_θ and β_θ even for the case for which evanescent modes must be included; if, however, $\underline{u}_t$ is chosen with the correct symmetry, $\underline{w}$ can be expanded in terms of the $\underline{\phi}_n$ and the question does not then arise.¹⁴

6. Lower bounds on α_θ and β_θ

The general procedure for obtaining lower bounds on α_θ and β_θ involves the use of comparison potentials for which the scattering problem can be solved exactly, and the monotonicity theorem, equation (20). A number of cases have been treated in the literature.^{6,7} In this section, we will consider just three special cases applicable to a wide variety of waveguide scattering problems. We restrict ourselves to waveguides which are of uniform cross-section everywhere. These three cases are particularly simple to apply.

In the context of the following discussion, metallic obstacles may be regarded as dielectric obstacles with infinite negative permittivity. (This comment does not apply to the preceding discussion of the variational principle and associated eigenvalue because the integrals would be divergent with an infinite 'potential'.) Suppose the obstacle does not extend beyond $z = \pm d$, and that ρ is identically zero for $|z| > d$ and positive for $|z| < d$.

We will first obtain a lower bound on β_θ . As μ approaches $-\infty$, it is

evident that the phase shift $\delta(\mu)$ of the associated eigenvalue problem approaches $-kd$ in the odd case and $-kd - \frac{1}{2}\pi$ in the even case. Now if $-kd > \Theta - \pi$ in the odd case or $-kd - \frac{1}{2}\pi > \Theta - \pi$ in the even case and if $\eta < \Theta$, then as shown in Figure 1, there can be no negative eigenvalues and β_Θ can be regarded as infinite. In this case the error term in equation (14) is always negative, and the variational approximation to $k \cot(\eta - \Theta)$ is always an upper bound on the exact value.

A lower bound on α_Θ can be obtained as follows. We know from the monotonicity theorem, equation (20), that the phase shift $\delta(\mu)$ is less than the phase shift $\delta'(\mu)$ which would result if the obstacle were replaced by a dielectric slab which fills the space $-d < z < d$ out to the conducting boundaries of the waveguide, and whose 'potential' is equal to the maximum value of $W + \mu\rho$. This phase shift is given by

$$\delta'_e(\mu) = -kd + \tan^{-1}\left(\frac{k'd}{kd} \tan k'd\right) \quad (28a)$$

$$\delta'_o(\mu) = -kd + \tan^{-1}\left(\frac{kd}{k'd} \tan k'd\right) \quad (28b)$$

$$k' = k'(\mu) = \left[k^2 + (W + \mu\rho)_{\max}\right]^{\frac{1}{2}} \quad (28c)$$

It can be seen from Figure 2 that a useful lower bound on α_Θ is provided by the value of μ , to be denoted by α'_Θ , defined by $\delta'(\alpha'_\Theta) \equiv \Theta$, provided that $\eta' \equiv \delta'(0) < \Theta$ and $\eta > \Theta - \pi$. For a dielectric obstacle η will always be greater than zero and the last condition will automatically be satisfied.

Figure 1

Determination of a lower bound on β_θ assuming $\eta < \theta$, and assuming $-kd > \theta - \pi$ in the odd case and $-kd - \frac{1}{2}\pi > \theta - \pi$ in the even case. Since $\delta(\mu)$ must exceed $\theta - \pi$, β_θ is infinite.

Figure 2

Determination of a lower bound on α_θ assuming $\eta' < \theta$ and $\eta > \theta - \pi$. The upper curve corresponds to a dielectric slab filling the guide in the range $-d < z < d$, whose 'potential' equals the maximum 'potential' of the obstacle. From the monotonicity theorem, $\delta'(\mu) > \delta(\mu)$ and therefore $\alpha_{\theta'} < \alpha_\theta$.

From the rough bounds already obtained on η ,

$$-kd - \frac{1}{2}\pi < \eta_e < \eta'_e \quad (29a)$$

$$-kd < \eta_o < \eta'_o \quad (29b)$$

it follows that a sufficient condition for obtaining lower bounds on α_θ and β_θ by the procedure described above is that $d(k^2 + W_{\max})^{\frac{1}{2}}$ be less than $\frac{1}{2}\pi$ in the even case and less than π in the odd case. An equivalent statement is that $2d$ must be less than $\frac{1}{2}\lambda$ in the even case and λ in the odd case, where λ is the smallest guide wavelength in the dielectric. However, it should be noted that these restrictions are by no means fundamental, since there are many more possibilities for obtaining lower bounds on α_θ and β_θ .

There is one case of interest in which β_θ can be determined exactly.⁶ If W is everywhere positive we can choose $\rho = W$. Then the 'potential' of the associated eigenvalue, $W + \mu\rho$, vanishes when $\mu = -1$ and the phase shift $\delta(-1)$ vanishes also. If we choose $\theta = 0$, it is evident that $\mu = -1$ is an eigenvalue. Furthermore, if we know that $\eta < \pi$, it is the smallest (in absolute value) negative eigenvalue as can be seen from Figure 3. Thus for the case in which $W > 0$, $\rho = W$, $\theta = 0$ and $\eta < \pi$, the eigenvalue β_o is given exactly by

$$\beta_o = 1 \quad (30)$$

(More generally, if $W > 0$, if $\rho = W$, and if $\eta < \theta$, then $\beta_\theta \geq 1$.)

Equation (30) is applied in Part 2 to a problem in which a special trial function is used which generates the Schwinger integral variational principle.

Figure 3

Determination of the exact value of β_0 assuming $W > 0$, $\rho = W$, $\theta = 0$ and $\eta < \pi$. In this case, β_0 is given exactly by $\beta_0 = 1$.

ACKNOWLEDGMENT

We would like to thank Dr. Martin Kelly and Leonard Rosenberg
for a helpful discussion.

REFERENCES

1. David S. Saxon, Notes on Lectures by Julian Schwinger: Discontinuities in Waveguides (Unpublished, 1945).
2. Nathan Marcuvitz, Waveguide Handbook (McGraw Hill Book Co., Inc., New York, 1951) M.I.T. Radiation Laboratory Series, Vol. 10.
3. B.A. Lippmann and J.S. Schwinger, Phys. Rev. 79, 469 (1950).
4. L. Hulthén, Kgl. Fysiograf. Sällskop. Lund. Forh. 14, 257 (1944).
5. H.S.W. Massey, Theory of Atomic Collisions. Encyclopedia of Physics, Vol. 36, Springer-Verlag, Berlin, 1957.
6. T. Kato, Progress of Theoretical Physics 6, 394 (1951).
7. L. Spruch, Phys. Rev. 109, 2149 (1958).
8. L. Spruch and M. Kelly, Phys. Rev. 109, 2144 (1958).
9. L. Spruch and L. Rosenberg, to be submitted for publication , considers scattering by compound system.
10. R. Bartram and L. Spruch, Bounds on the Elements of the Equivalent Network for Scattering in Waveguides. II. Applications to Dielectric Obstacles. New York University, Institute of Mathematical Sciences, Division of Electromagnetic Research, Report No. EM 133, 1959.
11. John M. Blatt and Victor F. Weisskopf. Theoretical Nuclear Physics (John Wiley and Sons, Inc., New York, and Chapman and Hall, Ltd., London, 1952).
12. C.G. Montgomery, R.H. Dicke and E.M. Purcell, Principles of Microwave Circuits (McGraw-Hill Book Co., Inc., New York, 1948) M.I.T. Radiation Laboratory Series, Vol. 8.

13. Philip M. Morse and Herman Feshbach, Methods of Theoretical Physics
(McGraw-Hill Book Co., Inc., New York, 1953) Part I, pp. 771-777.
14. Some further discussion on completeness is contained in reference 9.

DISTRIBUTION LIST FOR RESEARCH REPORTS

Contract No. AF 19(604)5238

(ONE copy unless otherwise noted)

<p>Commander Air Research and Development Command Andrews Air Force Base Washington 25, D. C. Attn: Major E. Wright, RDTCC</p> <p>Director of Resident Training 3380th Technical Training Group Keesler Air Force Base, Mississippi Attn: OA-3011 Course</p> <p>Director Air University Library Maxwell Air Force Base, Alabama</p> <p>Commander Air Force Missile Test Center Patrick Air Force Base, Florida Attn: MTE - for classified documents Attn: MU-411, Technical Library - for unclassified documents</p> <p>Tactical Air Group Directorate of Research and Development DCS/D Headquarters, USAF Washington, D. C. Attn: Major R. L. Stall</p> <p>Director, Communications and Electronics Hq. U. S. Air Force Washington 25, D. C. Attn: AFOAC S/E</p> <p>Commander Wright Air Development Center Wright-Patterson Air Force Base, Ohio Attn: WCLRS-6, Mr. Fortune</p> <p>Wright Air Development Center Wright-Patterson Air Force Base, Ohio Flight Research Laboratory Research Division Attn: WCRRA</p> <p>Commander Wright Air Development Center Wright-Patterson Air Force Base, Ohio Attn: N. Draganjac, WCLNQ-4</p> <p>Commander Wright Air Development Center Wright-Patterson Air Force Base, Ohio Attn: Mr. Paul Springer, WCLRE-5</p> <p>Commander Air Technical Intelligence Center Wright-Patterson Air Force Base, Ohio Attn: APCIN-1B1a</p> <p>Commander Rome Air Development Center Griffiss Air Force Base, New York Attn: RCSSTL-1</p> <p>Commander Rome Air Development Center Griffiss Air Force Base, New York Attn: Mr. Donald Dekan, RCUE</p> <p>Commander Rome Air Development Center (ARDC) Griffiss Air Force Base, New York Attn: Dr. John S. Burgess, RCE</p> <p>Commander Air Force Missile Development Center Holloman Air Force Base, New Mexico Attn: HDOIL, Technical Library</p> <p>Director U. S. Army Ordnance Ballistic Research Laboratories Aberdeen Proving Ground, Maryland Attn: Ballistic Measurements Laboratory</p> <p>Ballistic Research Laboratories Aberdeen Proving Ground, Maryland Attn: Technical Information Branch</p>	<p>Director Evans Signal Laboratory Belmar, New Jersey Attn: Mr. O. C. Woodyard</p> <p>U. S. Army Signal Engineering Labs. Evans Signal Laboratory Belmar, New Jersey Attn: Technical Document Center</p> <p>Massachusetts Institute of Technology Signal Corps Liaison Officer Cambridge 39, Mass. Attn: A. D. Bedrosian, Room 26-131</p> <p>Commanding General, SIGFM/EL-PC U. S. Army Signal Engineering Labs. Fort Monmouth, New Jersey Attn: Dr. Horst H. Kedesdy Deputy Chief, Chem-Physics Branch</p> <p>Commander Army Rocket and Guided Missile Agency Redstone Arsenal, Alabama Attn: Technical Library, ORDXR-OTL</p> <p>Commanding General U. S. Army Signal Engineering Labs. Fort Monmouth, New Jersey Attn: SIGFM/EL-AT</p> <p>Department of the Army Office of the Chief Signal Officer Washington 25, D. C. Attn: SIGRD-7</p> <p>Office of Chief Signal Officer Engineering and Technical Division Washington 25, D. C. Attn: SIGNET-5</p> <p>Guided Missile Fuze Library Diamond Ordnance Fuze Laboratories Washington 25, D. C. Attn: R. D. Hatcher, Chief Microwave Development Section</p> <p>(10) Armed Services Technical Information Agency Arlington Hall Station Arlington 12, Virginia</p> <p>(2) Library Boulder Laboratories National Bureau of Standards Boulder, Colorado</p> <p>National Bureau of Standards Department of Commerce Washington 25, D. C. Attn: Mr. A. G. McNish</p> <p>National Bureau of Standards Department of Commerce Washington 25, D. C. Attn: Gustave Shapiro, Chief Engineering Electronics Section Electricity and Electronics Div.</p> <p>(2) Office of Technical Services Department of Commerce Washington 25, D. C. Attn: Technical Reports Section (Unclassified only)</p> <p>Director National Security Agency Washington 25, D. C. Attn: R/D (331)</p> <p>(2) Hq. Air Force Cambridge Research Center Laurence G. Hanscom Field Bedford, Mass. Attn: CROTLR-2 - P. Condon</p> <p>(5) Hq. Air Force Cambridge Research Center Laurence G. Hanscom Field Bedford, Mass. Attn: J. Armstrong</p>	<p>(5) Hq. Air Force Cambridge Research Center Laurence G. Hanscom Field Bedford, Mass. Attn: CRRD</p> <p>Director, Avionics Division (AV) Bureau of Aeronautics Department of the Navy Washington 25, D. C.</p> <p>Chief, Bureau of Ships Department of the Navy Washington 25, D. C. Attn: Mr. E. Johnston, Coda 833E</p> <p>Commander U. S. Naval Air Missile Test Center Point Mugu, California Attn: Code 366</p> <p>U. S. Naval Ordnance Laboratory White Oak Silver Spring 19, Maryland Attn: The Library</p> <p>Commander U. S. Naval Ordnance Test Station China Lake, California Attn: Code 753</p> <p>Librarian U. S. Naval Postgraduate School Monterey, California</p> <p>Air Force Development Field Representative Naval Research Laboratory Washington 25, D. C. Attn: Coda 1072</p> <p>Director U. S. Naval Research Laboratory Washington 25, D. C. Attn: Code 2027</p> <p>Dr. J. J. Bohnert, Code 5210 U. S. Naval Research Laboratory Washington 25, D. C. (Unclassified only) Classified to be sent to: Director U. S. Naval Research Laboratory Attn: Code 5200 Washington 25, D. C.</p> <p>Commanding Officer and Director U. S. Navy Underwater Sound Laboratory Fort Trumbull, New London, Connecticut</p> <p>Chief of Naval Research Department of the Navy Washington 25, D. C. Attn: Code 427</p> <p>Commanding Officer and Director U. S. Navy Electronics Laboratory (Library) San Diego 52, California</p> <p>Chief, Bureau of Ordnance Department of the Navy Washington 25, D. C. Attn: Code Ad3</p> <p>Chief, Bureau of Ordnance Department of the Navy Surface Guided Missile Branch Washington 25, D. C. Attn: Coda ReS1-e</p> <p>Chief, Bureau of Ordnance Department of the Navy Washington 25, D. C. Attn: Fire Control Branch (ReS4)</p> <p>Department of the Navy Bureau of Aeronautics Technical Data Division, Code 4106 Washington 25, D. C.</p> <p>Chief, Bureau of Ships Department of the Navy Washington 25, D. C. Attn: Coda 817B</p>
---	---	--

Commanding Officer U. S. Naval Air Development Center Johnsville, Pennsylvania Attn: NADC Library	Convair, A Division of General Dynamics Corp. Fort Worth, Texas Attn: K.G. Brown, Division Research Librarian	General Electric Advanced Electronics Center Cornell University Ithaca, New York Attn: J. B. Travis
Commander U. S. Naval Air Test Center Patuxent River, Maryland Attn: ET-315, Antenna Branch	Convair, A Division of General Dynamics Corp. San Diego 12, California Attn: Mrs. Dora E. Burke, Engineering Librarian	General Electric Company Electronics Park Syracuse, New York Attn: Documents Library, B. Fletcher Building 3-143A
Director Naval Ordnance Laboratory Corona, California	Cornell Aeronautical Laboratory, Inc. 4455 Genesee Street Buffalo 21, New York Attn: Librarian	General Precision Laboratory, Inc. 63 Bedford Road Pleasantville, New York Attn: Mrs. Mary G. Herbst, Librarian
Commanding Officer U. S. Naval Ordnance Laboratory Corona, California Attn: Mr. W. Horenstein, Division 72	Dalmo Victor Company A Division of Textron, Inc. 1515 Industrial Way Belmont, California Attn: Marv Ellen Addams, Technical Librarian	Goodyear Aircraft Corp. 1210 Massillon Road Akron 15, Ohio Attn: Library D/120 Plant A
Airborne Instruments Laboratory, Inc. 160 Old Country Road Mineola, New York Attn: Dr. E. G. Fubini, Director Research and Engineering Division	Dorne and Margolin, Inc. 29 New York Avenue Westbury, Long Island, N. Y.	Granger Associates Electronic Systems 966 Commercial Street Palo Alto, California Attn: John V. N. Granger, President
Aircorn, Inc. 354 Main Street Winthrop, Mass.	Douglas Aircraft Company, Inc. P.O. Box 200 Long Beach 1, California Attn: Engineering Library (C-250)	Crumman Aircraft Engineering Corporation Bethpage, Long Island, N. Y. Attn: Mrs. A. M. Gray, Librarian Engineering Library, Plant No. 5
American Machine and Foundry Company Electronics Division 1085 Commonwealth Avenue Boston 15, Mass. Attn: Mrs. Rita Moravcsik, Librarian	Douglas Aircraft Co., Inc. 827 Lapham Street El Segundo, California Attn: Engineering Library	The Hallicrafters Company 4401 West 5th Avenue Chicago 24, Illinois Attn: LaVerne LaGioia, Librarian
Andrew Alford, Consulting Engineers 299 Atlantic Avenue Boston 10, Mass.	Douglas Aircraft Company, Inc. 3000 Ocean Park Boulevard Santa Monica, California Attn: P.T. Cline Eq. Sec. Reference Files, Eq. Eng. A250	Hoffman Laboratories, Inc. 3761 South Hill Street Los Angeles 7, California Attn: Engineering Library
Avion Division ACF Industries, Inc. 800 No. Pitt Street Alexandria, Virginia Attn: Library	Douglas Aircraft Company, Inc. 2000 North Memorial Drive Tulsa, Oklahoma Attn: Engineering Library, D-250	Hughes Aircraft Company Antenna Department Microwave Laboratory Building 12, Room 2617 Culver City, California Attn: M. D. Adcock
Battelle Memorial Institute 505 King Avenue Attn: Wayne E. Rife, Project Leader Electrical Engineering Division Columbus 1, Ohio	Electronics Communication, Inc. 1830 York Road Timonium, Maryland	Hughes Aircraft Company Florence and Teale Streets Culver City, California Attn: Dr. L.C. Van Atta, Associate Director Research Labs.
Bell Aircraft Corporation Post Office Box One Buffalo 5, New York Attn: Eunice P. Hazelton, Librarian	Emerson and Cuming, Inc. 869 Washington Street Canton, Mass. Attn: Mr. W. Cuming	Hycon Eastern, Inc. 75 Cambridge Parkway Cambridge, Mass. Attn: Mrs. Lois Seulowitz Technical Librarian
Bell Telephone Laboratories, Inc. Whippany Laboratory Whippany, New Jersey Attn: Technical Information Library	Emerson Electric Mfg. Co. 8100 West Florissant Avenue St. Louis 21, Missouri Attn: Mr. E.R. Breslin, Librarian	International Business Machines Corp. Military Products Division 530 Madison Avenue New York 33, New York Attn: Mr. C.F. McElwain, General Manager
Pacific Division Bendix Aviation Corporation 11600 Sherman Way North Hollywood, California Engineering Library Attn: Peggie Robinson, Librarian	Sylvania Elec. Prod. Inc. Electronic Defense Laboratory P.O. Box 205 - (Uncl) Mountain View, California Attn: Library	International Business Machines Corp. Military Products Division Owego, New York Attn: Mr. D. I. Marr, Librarian Department 459
Bendix Radio Division Bendix Aviation Corp. E. Joppa Road Towson 4, Maryland Attn: Dr. D. M. Allison, Jr. Director Engineering and Research	Fairchild Aircraft Division Fairchild Eng. and Airplane Corp. Hagerstown, Maryland Attn: Library	International Resistance Company 401 N. Broad Street Philadelphia 8, Pa. Attn: Research Library
Boeing Airplane Company Pilotless Aircraft Division P.O. Box 3707 Seattle 24, Washington Attn: R.R. Barber, Library Supervisor	Farnsworth Electronics Company 3700 East Pontiac Street Fort Wayne 1, Indiana Attn: Technical Library	Jansky and Bailey, Inc. 1339 Wisconsin Avenue, N. W. Washington 7, D. C. Attn: Mr. Delmer C. Ports
Boeing Airplane Company Wichita Division Engineering Library Wichita 1, Kansas Attn: Kenneth C. Knight, Librarian	Federal Telecommunication Labs. 500 Washington Avenue Nutley 10, New Jersey Attn: Technical Library	Dr. Henry Jasik, Consulting Engineer 298 Shames Drive Brush Hollow Industrial Park Westbury, New York
Boeing Airplane Company Seattle Division Seattle 14, Washington Attn: E.T. Allen, Library Supervisor	The Gabriel Electronics Division of the Gabriel Company 135 Crescent Road Needham Heights 94, Mass. Attn: Mr. Steven Galagan	Electromagnetic Research Corporation 711 14th Street, N. W. Washington 5, D. C.
Bjorksten Research Labs, Inc. P. O. Box 265 Madison, Wisconsin Attn: Mrs. Fern B. Korsgard		

Lockheed Aircraft Corporation
2555 N. Hollywood Way
California Division Engineering Library
Department 72-75, Plant A-1, Bldg. 63-1
Burbank, California
Attn: N. C. Harnois

The Martin Company
P. O. Box 179
Denver 1, Colorado
Attn: Mr. Jack McCormick

The Glenn L. Martin Company
Baltimore 3, Maryland
Attn: Engineering Library
Antenna Design Group

Marvland Electronic Manufacturing Corp.
5009 Calvert Road
College Park, Maryland
Attn: Mr. H. Warren Cooper

Mathematical Reviews
190 Hope Street
Providence 6, Rhode Island

The W. L. Maxson Corporation
460 West 34th Street
New York, N. Y.
Attn: Miss Dorothy Clark

McDonnell Aircraft Corporation
Lambert Saint-Louis Municipal Airport
Box 516, St. Louis 3, Missouri
Attn: R. D. Detrich, Engineering Library

McMillan Laboratory, Inc.
Brownville Avenue
Ipswich, Massachusetts
Attn: Security Officer, Document Room

Melpar, Inc.
3000 Arlington Boulevard
Falls Church, Virginia
Attn: Engineering Technical Library

Microwave Development Laboratory
90 Broad Street
Babson Park 57, Massachusetts
Attn: N. Tucker, General Manager

Microwave Radiation Company Inc.
19223 South Hamilton Street
Gardena, California
Attn: Mr. Morris J. Ehrlich, President

Chance Vought Aircraft, Inc.
9314 West Jefferson Street
Dallas, Texas
Attn: Mr. H. S. White, Librarian

Northrop Aircraft, Inc.
Hawthorne, California
Attn: Mr. E. A. Freitas, Library Dept 3145
1001 E. Broadway

Remington Rand Univ. - Division of Sperry
Rand Corporation
1900 West Allegheny Avenue
Philadelphia 29, Pennsylvania
Attn: Mr. John F. McCarthy
R and D Sales and Contracts

North American Aviation, Inc.
12214 Lakewood Boulevard
Downey, California
Attn: Engineering Library 495-115

North American Aviation, Inc.
Los Angeles International Airport
Los Angeles 45, California
Attn: Engineering Technical File

Page Communications Engineers, Inc.
710 Fourteenth Street, Northwest
Washington 5, D. C.
Attn: Librarian

Philco Corporation Research Division
Branch Library
4700 Wissachickon Avenue
Philadelphia 44, Pa.
Attn: Mrs. Dorothy S. Collins

Pickard and Burns, Inc.
240 Highland Avenue
Needham 94, Mass.
Attn: Dr. J. T. DeBettencourt

Polytechnic Research and Development
Company, Inc.
202 Tillary Street
Brooklyn 1, New York
Attn: Technical Library

Radiation Engineering Laboratory
Main Street
Maynard, Mass.
Attn: Dr. John Ruze

Radiation, Inc.
P. O. Drawer 37
Melbourne, Florida
Attn: Technical Library, Mr. M.L. Cox

Radio Corp. of America
RCA Laboratories
Rocky Point, New York
Attn: P. S. Carter, Lab. Library

RCA Laboratories
David Sarnoff Research Center
Princeton, New Jersey
Attn: Miss Fern Cloak, Librarian
Research Library

Radio Corporation of America
Defense Electronic Products
Building 10, Floor 7
Camden 2, New Jersey
Attn: Mr. Harold J. Schrader
Staff Engineer, Organization
of Chief Technical
Administrator

(2) The Ramo-Wooldridge Corporation
P.O. Box 45453 Airport Station
Los Angeles 45, California
Attn: Margaret C. Whitnah,
Chief Librarian

Hoover Microwave Co.
9592 Baltimore Avenue
College Park, Maryland

Director, USAF Project RAND
Via: Air Force Liaison Office
The Rand Corporation
1700 Main Street
Santa Monica, California

Rantec Corporation
Calsbasas, California
Attn: Grace Keener, Office Manager

Raytheon Manufacturing Company
Missile Systems Division
Bedford, Mass.
Attn: Mr. Irving Goldstein

Raytheon Manufacturing Company
Wayland Laboratory, State Road
Wayland, Mass.
Attn: Mr. Robert Borts

Raytheon Manufacturing Company
Wayland Laboratory
Wayland, Mass.
Attn: Miss Alice G. Anderson,
Librarian

Republic Aviation Corporation
Farmingdale, Long Island, N. Y.
Attn: Engineering Library

Thru: Air Force Plant Representative
Republic Aviation Corp.
Farmingdale, Long Island, N.Y.

Rheem Manufacturing Company
9236 East Hall Road
Downey, California
Attn: J. C. Joerger

Trans-Tech, Inc.
P. O. Box 346
Frederick, Maryland

Ryan Aeronautical Company
Lindbergh Field
San Diego 12, California
Attn: Library - unclassified

Sage Laboratories
159 Linden Street
Wellesley 81, Mass.

Sanders Associates
95 Canal Street
Nashua, New Hampshire
Attn: N. R. Wild, Librarian

Sandia Corporation, Sandia Base
P.O. Box 5800, Albuquerque, New Mexico
Attn: Classified Document Division

Sperry Gyroscope Company
Great Neck, Long Island, New York
Attn: Florence W. Turnbull, Engr. Librarian

Stanford Research Institute
Menlo Park, California
Attn: Library, Engineering Division

Sylvania Electric Products, Inc.
100 First Avenue
Waltham 54, Mass.
Attn: Charles A. Thornhill, Report Librarian
Waltham Laboratories Library

Systems Laboratories Corporation
14852 Ventura Boulevard
Sherman Oaks, California
Attn: Donald L. Margerum

TRG, Inc.
17 Union Square West
New York 3, N. Y.
Attn: M. L. Henderson, Librarian

A. S. Thomas, Inc.
161 Devonshire Street
Boston 10, Mass.
Attn: A. S. Thomas, President

Bell Telephone Laboratories
Murray Hill
New Jersey

Chu Associates
P. O. Box 387
Whitcomb Avenue
Littleton, Mass.

Microwave Associates, Inc.
Burlington, Mass.

Raytheon Manufacturing Company
Missile Division
Hartwell Road
Bedford, Mass.

Radio Corporation of America
Aviation Systems Laboratory
225 Crescent Street
Waltham, Mass.

Lockheed Aircraft Corporation
Missile Systems Division Research Library
Box 504, Sunnyvale, California
Attn: Miss Eva Lou Robertson,
Chief Librarian

The Rand Corporation
1700 Main Street
Santa Monica, California
Attn: Dr. W. C. Hoffman

Commander
AF Office of Scientific Research
Air Research and Development Command
14th Street and Constitution Avenue
Washington, D. C.
Attn: Mr. Otting, SRY

Westinghouse Electric Corp.
Electronics Division
Friendship Int'l Airport Box 746
Baltimore 3, Maryland
Attn: Engineering Library

Wheeler Laboratories, Inc.
122 Cutter Mill Road
Great Neck, New York
Attn: Mr. Harold A. Wheeler

Zenith Plastics Co.
Box 91
Gardena, California
Attn: Mr. S. S. Oleesky

Library Geophysical Institute
of the University of Alaska
College
Alaska

University of California
Berkeley 4, California
Attn: Dr. Samuel Silver,
Prof. Engineering Science
Division of Elec. Eng. Electronics
Research Lab.

University of California
Electronics Research Lab.
332 Cory Hall
Berkeley 4, California
Attn: J. R. Whinnery

California Institute of Technology
Jet Propulsion Laboratory
4800 Oak Grove Drive
Pasadena, California
Attn: Mr. I. E. Newlan

California Institute of Technology
1201 E. California Street
Pasadena, California
Attn: Dr. C. Papas

Carnegie Institute of Technology,
Schenley Park
Pittsburgh 13, Pennsylvania
Attn: Prof. A. E. Heins

Cornell University
School of Electrical Engineering
Ithaca, New York
Attn: Prof. G. C. Dalman

University of Florida
Department of Electrical Engineering
Gainesville, Florida
Attn: Prof. M. H. Latour, Librarian

Library
Georgia Institute of Technology
Engineering Experiment Station
Atlanta, Georgia
Attn: Mrs. J.H. Crosland, Librarian

Harvard University
Technical Reports Collection
Gordon McKay Library, 303A Pierce Hall
Oxford Street, Cambridge 38, Mass.
Attn: Mrs. E.L. Rufschnidt, Librarian

Harvard College Observatory
60 Garden Street
Cambridge 39, Mass.
Attn: Dr. Fred L. Whipple

University of Illinois
Documents Division Library
Urbana, Illinois

University of Illinois
College of Engineering
Urbana, Illinois
Attn: Dr. P. E. Moyes, Department of
Electrical Engineering

The Johns Hopkins University
Homewood Campus
Department of Physics
Baltimore 18, Maryland
Attn: Dr. Donald E. Kerr

Sandia Corporation
Attn: Organization 1423
Sandia Base
Albuquerque, New Mexico

Applied Physics Laboratory
The Johns Hopkins University
8621 Georgia Avenue
Silver Spring, Maryland
Attn: Mr. George L. Seielstad

Massachusetts Institute of Technology
Research Laboratory of Electronics
Room 20B-221
Cambridge 39, Massachusetts
Attn: John H. Hewitt

Massachusetts Institute of Technology
Lincoln Laboratory
P. O. Box 73
Lexington 73, Mass.
Attn: Document Room A-229

University of Michigan
Electronic Defense Group
Engineering Research Institute
Ann Arbor, Michigan
Attn: J. A. Boyd, Supervisor

University of Michigan
Engineering Research Institute
Radiation Laboratory
Attn: Prof. K. M. Siegel
912 N. Main St.,
Ann Arbor, Michigan

University of Michigan
Engineering Research Institute
Willow Run Laboratories
Willow Run Airport
Ypsilanti, Michigan
Attn: Librarian

University of Minnesota
Minneapolis 14, Minnesota
Attn: Mr. Robert H. Stumm, Library

Northwestern University
Microwave Laboratories
Evanston, Illinois
Attn: R. E. Beam

Ohio State University Research Found.
Ohio State University
Columbus 10, Ohio
Attn: Dr. T.E. Tice
Dept. of Elec. Engineering

The University of Oklahoma
Research Institute
Norman, Oklahoma
Attn: Prof. C. L. Farrar, Chairman
Electrical Engineering

Polytechnic Institute of Brooklyn
Microwave Research Institute
55 Johnson Street
Brooklyn, New York
Attn: Dr. Arthur A. Oliner

Polytechnic Institute of Brooklyn
Microwave Research Institute
55 Johnson Street
Brooklyn, New York
Attn: Mr. A. E. Laemmel

Syracuse University Research Institute
Cortland Campus
Syracuse 10, New York
Attn: Dr. C. S. Grove, Jr.
Director of Engineering Research

The University of Texas
Elec. Engineering Research Laboratory
P. O. Box 8026, University Station
Austin 12, Texas
Attn: Mr. John R. Gerhardt
Assistant Director

The University of Texas
Defense Research Laboratory
Austin, Texas
Attn: Claude W. Horton, Physics Library

University of Toronto
Department of Electrical Engineering
Toronto, Canada
Attn: Prof. G. Sinclair

Lowell Technological Institute
Research Foundation
P. O. Box 709, Lowell, Mass.
Attn: Dr. Charles R. Mingins

University of Washington
Department of Electrical Engineering
Seattle 5, Washington
Attn: G. Held, Associate Professor

Stanford University
Stanford, California
Attn: Dr. Chodorow
Microwave Laboratory

Physical Science Laboratory
New Mexico College of Agriculture
and Mechanic Arts
State College, New Mexico
Attn: Mr. H. W. Haas

Brown University
Department of Electrical Engineering
Providence, Rhode Island
Attn: Dr. C. M. Angulo

Case Institute of Technology
Cleveland, Ohio
Attn: Prof. S. Seeley

Columbia University
Department of Electrical Engineering
Morningside Heights
New York, N. Y.
Attn: Dr. Schlesinger

McGill University
Montreal, Canada
Attn: Prof. G. A. Woonton
Director, The Eaton Electronics
Research Lab.

Purdue University
Department of Electrical Engineering
Lafayette, Indiana
Attn: Dr. Schultz

The Pennsylvania State University
Department of Electrical Engineering
University Park, Pennsylvania

University of Pennsylvania
Institute of Cooperative Research
3400 Walnut Street
Philadelphia, Pennsylvania
Attn: Dept. of Electrical Engineering

University of Tennessee
Ferris Hall
W. Cumberland Avenue
Knoxville 16, Tennessee

University of Wisconsin
Department of Electrical Engineering
Madison, Wisconsin
Attn: Dr. Scheibe

University of Seattle
Department of Electrical Engineering
Seattle, Washington
Attn: Dr. D. K. Reynolds

Wayne University
Detroit, Michigan
Attn: Prof. A. F. Stevenson

Electronics Research Laboratory
Illinois Institute of Technology
3300 So. Federal Street
Chicago 16, Illinois
Attn: Dr. Lester C. Peach
Research Engineer

Advisory Group on Electronic Parts
Room 103
Moore School Building
200 South 33rd Street
Philadelphia 4, Pennsylvania

Ionosphere Research Laboratory
Pennsylvania State College
State College, Pennsylvania
ATTN: Professor A. H. Waynick, Director

Institute of Mathematical Sciences
25 Waverly Place
New York 3, New York
ATTN: Librarian

Electronics Division
Rand Corporation
1700 Main Street
Santa Monica, California
ATTN: Dr. Robert Kalaba

National Bureau of Standards
Washington, D. C.
ATTN: Dr. W. K. Saunders

Applied Mathematics and Statistics Lab.
Stanford University
Stanford, California
ATTN: Dr. Albert H. Bowker

Department of Physics and Astronomy
Michigan State College
East Lansing, Michigan
ATTN: Dr. A. Leitner

University of Tennessee
Knoxville, Tennessee
ATTN: Dr. Fred A. Picken

Lebanon Valley College
Annville, Pennsylvania
ATTN: Professor B.H. Bissinger

General Atomic
P. O. Box 608
San Diego 12, California
Attn: Dr. Edward Gerjuoy

Department of Physics
Amherst College
Amherst, Mass.
ATTN: Dr. Arnold Arons

California Institute of Technology
1201 E. California Street
Pasadena, California
ATTN: Dr. A. Erdelyi

Mathematics Department
Stanford University
Stanford, California
ATTN: Dr. Harold Levine

University of Minnesota
Minneapolis 14, Minnesota
ATTN: Professor Paul C. Rosenbloom

Department of Mathematics
Stanford University
Stanford, California
ATTN: Professor Bernard Epstein

Applied Physics Laboratory
The Johns Hopkins University
8621 Georgia Avenue
Silver Spring, Maryland
ATTN: Dr. B. S. Courary

(2) Exchange and Gift Division
The Library of Congress
Washington 25, D. C.

Electrical Engineering Department
Massachusetts Institute of Technology
Cambridge 39, Mass.
ATTN: Dr. L. J. Chu

Nuclear Development Associates, Inc.
5 New Street
White Plains, New York
ATTN: Library

California Institute of Technology
Electrical Engineering
Pasadena, California
ATTN: Dr. Zohrab A. Kaprielian

Dr. Rodman Doll
311 W. Cross Street
Ypsilanti, Michigan

California Inst. of Technology
Pasadena, California
ATTN: Mr. Calvin Wilcox

(3) Mr. Robert Brockhurst
Woods Hole Oceanographic Institute
Woods Hole, Mass.

National Bureau of Standards
Boulder, Colorado
ATTN: Dr. R. Gallet

Dr. Solomon L. Schwebel
3689 Louis Road
Palo Alto, California

University of Minnesota
The University of Library
Minneapolis 14, Minnesota
ATTN: Exchange Division

Department of Mathematics
University of California
Berkeley, California
ATTN: Professor Bernard Friedman

Lincoln Laboratory
Massachusetts Institute of Technology
P. O. Box 73
Lexington 73, Massachusetts
ATTN: Dr. Shou Chin Wang, Room C-351

Melpar, Inc.,
3000 Arlington Boulevard
Falls Church, Virginia
ATTN: Mr. K. S. Kelleher, Section Head

Hq. Air Force Cambridge Research Center
Laurence G. Hanscom Field
Bedford, Mass.
ATTN: Mr. Francis J. Zucker, CRRD

Hq. Air Force Cambridge Research Center
Laurence G. Hanscom Field
Bedford, Mass.
ATTN: Dr. Philip Newman, CRRK

Mr. N. C. Gerson
Trapelo Road
South Lincoln, Mass.

Dr. Richard B. Barrar
Systems Development Corp.
2400 Colorado Avenue
Santa Monica, California

Columbia University Hudson Laboratories
P.O. Box 239
145 Palisade Street, Dobbs Ferry, N. Y.
ATTN: Dr. N. W. Johnson

Institute of Fluid Dynamics
and Applied Mathematics
University of Maryland
College Park, Maryland
ATTN: Dr. Elliott Montroll

Department of Electrical Engineering
Washington University
Saint Louis 5, Mo.
ATTN: Professor J. Van Bladel

Department of the Navy
Office of Naval Research Branch Office
1030 E. Green Street
Pasadena 1, California

Brandeis University
Waltham, Mass.
ATTN: Library

General Electric Company
Microwave Laboratory
Electronics Division
Stanford Industrial Park
Palo Alto, California
ATTN: Library

Smyth Research Associates
3555 Aero Court
San Diego 3, California
ATTN: Dr. John B. Smyth

Electrical Engineering
California Institute of Technology
Pasadena, California
ATTN: Dr. Georges C. Weill

Naval Research Laboratory
Washington 25, D. C.
ATTN: Henry J. Passerini, Code 5278A

Dr. George Kear
5 Culver Court
Orinda, California

Brooklyn Polytechnic
85 Livingston Street
Brooklyn, New York
ATTN: Dr. Nathan Marcuvitz

Department of Electrical Engineering
Brooklyn Polytechnic
85 Livingston Street
Brooklyn, New York
ATTN: Dr. Jerry Shmoys

Department of Mathematics
University of New Mexico
Albuquerque, New Mexico
ATTN: Dr. I. Kolodner

Mathematics Department
Polytechnic Institute of Brooklyn
Johnson and Jay Street
Brooklyn, New York
ATTN: Dr. Harry Hochstadt

Ballistics Research Laboratory
Aberdeen Proving Grounds
Aberdeen, Maryland
ATTN: Dr. Pullen Keata

Dr. Lester Kraus
4935 Whitehaven Way
San Diego, California

University of Minnesota
Institute of Technology
Minneapolis, Minnesota
Attn: Dean Athelston Spilhaus

Ohio State University
Columbus, Ohio
Attn: Prof. C. T. Tai
Department of Electrical Eng.

Naval Research Laboratories
Washington 25, D. C.
Attn: W. S. Ament, Code 5271

Naval Research Laboratory
Washington 25, D. C.
Attn: Dr. Leslie G. McCracken, Jr.
Code 3933A

Office of Naval Research
Department of the Navy
Attn: Geophysics Branch, Code 416
Washington 25, D. C.

Office of Chief Signal Officer
Signal Plans and Operations Division
Attn: SIGOL-2, Room 20
Com. Liaison Br., Radio Prop. Sect.
The Pentagon, Washington 25, D. C.

Defence Research Member
Canadian Joint Staff
2001 Connecticut Street
Washington, D. C.

Central Radio Prop. Lab.
National Bureau of Standards
Attn: Technical Reports Library
Boulder, Colorado

U. S. Weather Bureau
U. S. Department of Commerce
Washington 25, D. C.
Attn: Dr. Harry Wexler

Federal Communications Commission
Washington 25, D. C.
Attn: Mrs. Barbara C. Grimes, Librarian

Upper Atmosphere Research Section
Central Radio Propagation Laboratory
National Bureau of Standards
Boulder, Colorado

Argonne National Laboratory
P.O. Box 299
Lemont, Illinois
Attn: Dr. Hoylande D. Young

Bell Telephone Labs.
Murray Hill, New Jersey
Attn: Dr. S. O. Rice, 3B - 203

Carnegie Institute of Washington
Dept. of Terrestrial Magnetism
5241 Broad Branch Road, N. W.
Washington 15, D. C.
Attn: Library

Georgia Tech Research Institute
225 N. Avenue, N. W.
Attn: Dr. James E. Boyd
Atlanta, Georgia

University of Maryland
College Park, Maryland
Attn: Dr. A. Weinstein
Institute of Fluid Dynamics

Massachusetts Institute of Technology
Lincoln Laboratory
P. O. Box 73
Lexington 73, Massachusetts
Attn: Prof. Radford, Division 3 Head

Willow Run Research Center
University of Michigan
Willow Run Airport
Ypsilanti, Michigan
Attn: Dr. C. L. Dolph

School of Engineering
New York University
University Heights
New York, New York

Shell Fellowship Committee of the
Shell Companies Foundation, Inc.
50 West 50th Street
New York 20, N. Y.
Attn: Mr. J. R. Janssen

Esso Research and Engineering Co.
P. O. Box 51
Linden, New Jersey
Attn: Mr. C. L. Brown, Manager

Union Carbide and Carbon Corp.
30 E. 42nd Street
New York 17, New York
Attn: Mr. L. E. Erlandson

Convair
San Diego 12, California
Attn: Mr. Marvin Stern

Bell Telephone Labs., Inc.
463 West Street
New York 13, N. Y.
Attn: Dr. Mervin J. Kelly

Engineering Library
University of California
405 Hilgard Avenue
Los Angeles 24, California

Convair, A Division of General Dynamics Corp.
Daingerfield, Texas
Attn: J. E. Arnold, Division Manager

Convair, A Division of General Dynamics Corp.
San Diego 12, California
Attn: R. L. Bayless, Chief Engineer

Convair, a Division of General Dynamics Corp.
San Diego 12, California
Attn: K. J. Bossart, Chief Engineer-WS107A

Convair, A Div. of General Dynamics
Corp.
Fort Worth 1, Texas
Attn: F. W. Davis, Chief Engineer

Convair, A Div. of General Dynamics
Corp.
Pomona, California
Attn: C. D. Perrine
Ass't Div. Manager, Engin.

Shell Development Company
Exploration and Production Res. Div.
3737 Bellshire Boulevard
Houston 25, Texas
Attn: Miss Aphrodite Mamoulides

RCA Laboratories
Princeton, New Jersey
Attn: Dr. Charles Polk

Stanford Research Institute
S. Pasadena, California
Attn: Dr. J. Brandstatten

Wayne State University
Kresge-Hooker Science Library
5250 Second Boulevard
Detroit 2, Michigan

ARRA
1 Bond Street
Westbury, L. I., New York
Attn: Dr. Norman Spector

Varian Associates
611 Hansen Way
Palo Alto, California
Attn: Mrs. Perry Conway
Technical Librarian

Case Institute of Technology
Department of Electrical Engin.
University Circle
Cleveland 6, Ohio
Attn: Prof. Robert Plonsey

Dr. Ming S. Wong, CRKRP
Air Force Cambridge Research Center
Laurence G. Hanscom Field
Bedford, Massachusetts

Physics Section
AVCO-RAD Division
20 South Union Street
Lawrence, Mass.
Attn: Dr. Ernest Bauer

Advanced Development Section
Western Development Labs.
Philco Corp.
3875 Fabian Way
Palo Alto, California
Attn: Dr. Albert R. Giddis

Department of Aeronautical Engineering
University of Michigan
Ann Arbor, Michigan
Attn: Prof. Mahinder Uberoi

Gordon McKay Laboratory
Harvard University
Cambridge 39, Mass.
Attn: Dr. S. R. Seshadri

Commander
Air Research and Development Command
Attn: RDTR
Andrews Air Force Base
Washington 25, D. C.

College of Engineering
Dept. of Electrical Engineering
University of Florida
Gainesville, Florida
Attn: Dr. Sullivan

Dr. V. M. Papadopoulos
Dept. of Engineering
Brown University
Providence, R. I.

Major Vernon Lee Dawson
RSDD-OML(MO)
Redstone Arsenal
Huntsville, Alabama

Grumman Aircraft Engineering Corp.
South Oyster Bay Road
Bethpage, Long Island, N. Y.
Attn: Dr. Charles Mack

AF Office of Scientific Research
Washington 25, D. C.
Attn: Dr. Karl Kaplan

University of California
Radiation Laboratory
P. O. Box 808
Livermore, California
Attn: Dr. Bernard A. Lippmann

Department of Electrical Engineering
Case Institute of Technology
University Circle
Cleveland 6, Ohio
Attn: Professor Albert E. Collin

Antenna Laboratory
Air Force Cambridge Research Center
Laurence G. Hanscom Field
Bedford, Massachusetts
Attn: Mr. Philip Blackstone

Lt. Mark J. Beran, CRRD
Air Force Cambridge Research Center
Laurence G. Hanscom Field
Bedford, Massachusetts

Mr. Richard Mack, CRRD
Air Force Cambridge Research Center
Laurence G. Hanscom Field
Bedford, Massachusetts

System Development Corporation
2500 Colorado Avenue
Santa Monica, California
Attn: Library

[illegible]

NYU

EM-

132 Spruch.

Bounds on the elements of
the equivalent network for
scattering in waveguides.
I: Theory

NYU

EM-

132 Spruch.

Bounds on the elements of
the equivalent network for
scattering in waveguides.
I: Theory.

**N. Y. U. Institute of
Mathematical Sciences**

25 Waverly Place
New York 3, N. Y.